

TILLERS 2025



Tillers 2025



5–7,5 hp	FM-511MX	SL-51	FM-633M	SL-61	FM-811MB	SL-85B (AS1529-8)
	★	★	★★	★★	★★	★★
Engine	petrol	petrol	petrol	petrol	petrol	petrol
Rated Power	5 hp	5 hp	7,5 hp	8 hp	7,5 hp	7,5 hp
Fuel tank, capacity	1,3 L	1,3 L	3,6 L	3,6 L	3,6 L	3,6 L
Oil sump capacity	0,35 L	0,35 L	0,6 L	0,6 L	0,6 L	0,6 L
Gearbox	worm	worm	chain	chain	chain	chain
Clutch	belt	belt	belt	belt	belt	belt
PTO (power take-off shaft)	no	no	no	no	no	no
Number of speeds	1 forward	1 forward	1 forward + 1 reverse	1 forward + 1 reverse	2 forward + 1 reverse	2 forward + 1 reverse
Low gear	no	no	no	no	no	no
Drive shaft type	● 20 mm	● 20 mm	● 30 mm	● 30 mm	● 23 mm	● 23 mm
Cutting width	56 cm	56 cm	30 / 55 / 85 cm	30 / 55 / 85 cm	75 / 95 cm	75 / 95 cm
Cultivation depth	up to 24 cm	up to 24 cm	up to 30 cm	up to 30 cm	up to 30 cm	up to 30 cm
Nominal productivity*	2 acres/h	2 acres/h	3,5 acres/h	3,5 acres/h	4,5 acres/h	4,5 acres/h
Plant protection discs	yes	yes	no	no	yes	no
Wheels included	no	no	no	no	4.00-8	no
Interwheel distance	no	no	no	no	60 cm	60 cm
Tool box	no	no	no	no	no	no
Gross weight with wheels	38 kg	38 kg	54 kg	54 kg	98 kg	88 kg
Box dimensions L×W×H	71×38×66 cm	71×38×66 cm	75×41×59 cm	75×41×59 cm	80×40×100 cm	80×40×100 cm

*productivity is indicated for medium-density soil at maximum speed. Productivity can vary depending on type of soil, speed of work and other factors.

Tillers 2025



7,5–18 hp

SL-85BL
(AS2312-1)

FM-808MXL
(FM2211-1)

SL-84L

FM-1617MXL

SL-186L

SL-187L
(AS1556-1)



Engine	petrol	petrol	petrol	petrol	petrol	petrol
Rated Power	7,5 hp	8 hp	8 hp	16 hp	18 hp	18 hp
Fuel tank, capacity	3,6 L	6 L	6 L	6 L	6 L	6 L
Oil sump capacity	0,6 L	0,6 L	0,6 L	1,1 L	1,1 L	1,1 L
Gearbox	chain	gear	gear	gear	gear	gear
Clutch	belt	multi-disc	multi-disc	multi-disc	multi-disc	multi-disc
PTO (power take-off shaft)	no	no	no	no	no	no
Number of speeds	4 forward + 2 reverse	3 forward + 1 reverse	3 forward + 1 reverse	3 forward + 1 reverse	4 forward + 1 reverse	3 forward + 1 reverse
Low gear	yes	yes	yes	yes	yes	yes
Drive shaft type	23 mm	23 mm	23 mm	32 mm	32 mm	32 mm
Cutting width	85 / 95 cm	85 / 105 cm	85 / 105 cm	85 / 105 cm	115 / 135 cm	115 / 135 cm
Cultivation depth	up to 30 cm	up to 30 cm	up to 30 cm	up to 30 cm	up to 30 cm	up to 30 cm
Nominal productivity*	4,5 acres/h	6,5 acres/h	6,5 acres/h	8,5 acres/h	10 acres/h	10 acres/h
Plant protection discs	no	no	no	no	no	no
Wheels included	no	no	no	no	no	no
Interwheel distance	60 cm	60 cm	60 cm	60 cm	60 cm	60 cm
Tool box	no	no	yes	no	no	no
Gross weight with wheels	70 kg	96 kg	96 kg	115 kg	115 kg	115 kg
Box dimensions L×W×H	78×38×105 cm	82×45×66 cm	82×45×66 cm	78×53×95 cm	78×53×95 cm	78×53×95 cm

*productivity is indicated for medium-density soil at maximum speed. Productivity can vary depending on type of soil, speed of work and other factors.

Accessories compatibility



Ferremer FM-811MB

Asilak SL-85B / SL-85BL

Asilak SL-84L

Ferremer FM-808MXL

Ferremer FM-1617MXL

Asilak SL-186L

Asilak SL-187L

Rated Power
PTO (power take-off shaft)

7,5 hp

7,5 hp

8 hp

8 hp

16 hp

16 hp

18 hp

Number of speeds

2 forward + 1 reverse

2 forward + 1 reverse

3 forward + 1 reverse

3 forward + 1 reverse

3 forward + 1 reverse

4 forward + 1 reverse

3 forward + 1 reverse

Drive shaft type

23 mm

23 mm

23 mm

23 mm

32 mm

32 mm

32 mm

Cutting width

75 / 95 cm

75 / 95 cm

85 / 105 cm

85 / 105 cm

85 / 105 cm

115 / 135 cm

115 / 135 cm

TUBES

4.00-8

SL-A8201 (01)

4.00-10

SL-A8213 (02)

5.00-12

SL-A8202 (03)

6.00-12 / 6.50-12

SL-A8203 (04)

TYRES

4.00-8

SL-A8204 / SL-A8214 (05)

5.00-12

SL-A8205 / SL-A8215 (06)

6.50-12

SL-A8206 / SL-A8216 (07)

WHEELS

4.00-8

SL-A8207 (08)

4.00-10

SL-A8212 (09)

5.00-12

SL-A8208 (10)

6.50-12

SL-A8209 (11)

EASY TURN PLATE

SL-A8211 (12)

TUBES



TYRES



WHEELS



EASY TURN PLATE

